

OLYMPUS®

Your Vision, Our Future

STEREOMICROSCOPE

SZX7/SZ61/SZ51

For Industrial Use



Specifications are subject to change without any obligation on the part of the manufacturer.

OLYMPUS®

www.olympus.com

OLYMPUS OPTICAL CO., LTD.
San-Ei building, 22-2, Nishi Shinjuku 1-chome, Shinjuku-ku, Tokyo, Japan
OLYMPUS OPTICAL CO. (EUROPA) GMBH.
Postfach 10 49 08, 20034, Hamburg, Germany
OLYMPUS INDUSTRIAL AMERICA, INC.
1 Corporate Drive, Orangeburg, NY 10962, U.S.A.
OLYMPUS SINGAPORE PTE LTD.
491B River Valley Road, #12-01/04 Valley Point Office Tower, Singapore 248373

OLYMPUS OPTICAL CO. (U.K.) LTD.
2-8 Honduras Street, London EC1Y 0TX, United Kingdom.
OLYMPUS AUSTRALIA PTY. LTD.
31 Gilby Road, Mt. Waverley, VIC 3149, Melbourne, Australia.

Comfort for your eyes — precision for your work

The human eye is a wonderful instrument, catching images of every moment of our lives. At the same time it is extremely sensitive, and can become exhausted if it is not treated with care.

OLYMPUS has therefore made every possible effort to develop new optical systems that allow the human eye to feel comfortable and relaxed while working with stereo microscopes. This not only protects the eyes but also leads to much more precise and consistent results in daily work.

All three models — the SZX7 with its advanced Galilean optical system, the full-featured SZ61 and the versatile SZ51 — provide 3D images with true color, high resolution and no distortion.

Welcome to the comfort zone.



CONTENTS

"Comfort Zone"	1 - 12
• Optical	
• Ergonomy	
• Illumination	
• Digital Imaging	
• Mounting System & Accessories	
Specifications	13-14
System diagram, dimensions & weight SZX7	15 - 16
System diagram, dimensions & weight SZ61/SZ51	17 - 18

SZX7: Galilean optical system using parallel light paths for outstanding performance and easy expandability.

SZ61: Top-of-the-line optical performance, with 1:6.7 zoom ratio.
Model variations: SZ61-TR (with trinocular tube),
SZ61-60 (with 60 degree observation tube inclination).

SZ51: Versatile, cost-efficient, ideal in all line inspection applications.

Optical excellence and system expandability — SZX7 with Galilean optics

“Providing the optimal image for any specimen” by the adoption of the Galilean optical system and the DF (Distortion Free) objective lens series with maximum N.A. (Numerical Aperture).

The best zoom ratio in this class

With a magnification range of 8x-56x (using 1x objective/10x eyepiece), the SZX7 offers a maximum zoom ratio of 1:7. This is the best in its class, and allows any given specimen to be observed at the most appropriate magnification.

The best resolving power in this class

Superior quality objectives deliver accurate, high resolution observation images which show every specimen in minute detail.

A range of objectives to suit every specimen and every application

- **Superior image flatness:**

The DFPlan objective series accurately reproduces the original shape of the specimen.

- **Longest working distance (W.D.) in this class:**

The objectives range from the SZX-ACH1x (90mm W.D.) to the DFPL0.5x (198mm W.D.). As a result, even specimen surfaces which are difficult to access can be observed easily.

- **Ideal for high magnification:**

Superior quality image is ensured up to 336x, by combining a 2x objective with 30x eyepieces.



Galilean optics feature two (right/left) independent and parallel zoom optical paths to produce the focal point with one objective lens. The system enables high optical performance as well as functional modularity.



“ComfortView” eyepieces for greater comfort and faster work

Quick, comfortable observation and documentation are ensured by this completely new eyepiece design featuring Pupil Aberration Control and Appropriate Positioning in the eye point.

Accurate color reproduction

The careful selection of lens surface coating and glass materials in the entire optical system make it possible to observe and document specimens in their original, authentic colors.

Sharp, clear, high-contrast images

The low, suppressed field curvature ensures accurate reproduction of original specimen shapes.

A wide variety of observation tubes and intermediate tubes enable operators to obtain precisely the right image

Various different types of tubes are available, and can be freely combined to create the ideal system for any specified purpose.

SZX7 tubes:

- Aperture diaphragm unit / SZX-AS
- Beam splitter / SZX-BS
- Eyepoint adjuster / SZX-EPA
- Filter adapter / SZX-FAD
- Macro tube / SZX-DA
- Photo adapter / SZX-PHA
- Side by side discussion tube / SZX-SDO



Aperture diaphragm unit / SZX-AS



① 45 degree binocular head / SZX-BI45 ② Tilting binocular head / SZX-TBI ③ 30 degree trinocular head / SZX-TR30

Precise, functional and compact — SZ61/SZ51

“A practical range of functions for observation and documentation in a compact stereo microscope body”
The SZ61/SZ51, incorporating the Greenough optical system.

1:6.7 — the best zoom ratio in this class

The SZ61's class-leading magnification range extends from 6.7 through 45x (using 10x eyepiece), with a zoom ratio of 1:6.7. This derives from the newly developed optical system and allows quick, comfortable observations at the most appropriate magnification. The SZ51 provides a magnification range from 8x through 40x (using 10x eyepiece), with a zoom ratio of 1:5.

Outstanding depth of focus and flatness

The 10-degree angle convergence of the image forming path in the Greenough optical system secures excellent image flatness with deep depth of focus.

“Comfort View” eyepieces for greater comfort and faster work

Quick, comfortable observation and documentation are ensured by this completely new eyepiece design featuring Pupil Aberration Control and Appropriate Positioning in the eye point.

Accurate color reproduction

The careful selection of lens surface coating and glass materials in the entire optical system make it possible to observe and document the specimen in their original, authentic colors.

Sharp, clear, high-contrast images

The low, suppressed field curvature ensures accurate reproduction of original specimen shapes.



The Greenough optical system has two zoom optical paths inclined at an inward angle. This enables a more compact microscope design while maintaining high performance.



Five zoom body variations with high performance

The SZ61 and SZ51 zoom bodies provide two different magnification ranges. They are available with an ergonomically designed 45-degree inclination tube for the use on the standard stands. For special applications where the zoom body has to be tilted for use with other equipment or mounting on a universal stand, models with 60-degree inclination tube (SZ61-60/SZ51-60) are available. For documentation purposes, OLYMPUS also offers the SZ61TR, which incorporates a trinocular tube for easy attachment of digital and video cameras.

Wide choice of auxiliary objectives

A wide choice of auxiliary objectives enables observations at magnifications from 1.6x to 270x and W.D. up to 400mm to comply with every application purpose.



SZ61/SZ51



SZ61-60/SZ51-60



SZ61-TR

Work more comfortably...and more productively

The Olympus approach to ergonomic design seeks to achieve improvements that make work easier, more comfortable, and more productive, all at the same time. That means applying advanced technological methods to maximizing operability, reducing factors that contribute to operator fatigue, and building in effective safety features like ESD design.

Ergonomic design based on 3D CAD analysis

The microscope body and stand feature a design of precisely curved contours developed through careful 3D CAD analysis. Key ergonomic features include an all-round finish that's smooth to the touch and helps to reduce fatigue in long period observations.

Convenient front-access operation

Improved ease of access to the most frequently used knobs and switches maximizes operator comfort and reduces back strain.

Tilting binocular tube for comfortable observations (SZX7)

A comfortable position that minimizes the risk of back strain and muscle tension promotes productivity and quality in routine inspection tasks. The continuously adjustable tilting binocular tube helps the operator to quickly find the most comfortable eyepoint position.

Precise recall of specific magnification settings via integrated click-stop mechanism (SZX7) or zoom knob stopper (SZ61/SZ51)

Many inspection tasks require the use of the same zoom magnification setting to ensure consistent and comparable

results. The integrated click-stop mechanism provides quick and easy access to this important function. The zoom knob stopper allows the user to choose magnification that can be quickly repeated, and the setting in use is clearly displayed on the front control panel.

New eyepiece reduces fatigue and excludes dust

This eyepiece features a pupillary aberration control mechanism whereby the image remains visible even if the operator's eyes move. This has been found to lessen operator fatigue in long lasting observations. The unique eyepiece mounting design excludes dust particles and keep the eyepiece firmly in place ensuring clear images and best eyepiece position.

ESD safety design

The increasing miniaturization and complexity of electronic devices raises the risk of damage by electric shock caused by electrostatic discharge. For this reason, OLYMPUS has taken special measures to design its stereo microscope bodies and main accessories to discharge static electricity from 1000V down to 10V in less than 0.2 seconds, protecting the equipment and preventing damage to samples.



LED Transmitted / Reflected Light Illumination Stand



Tilting binocular head (SZX7)



Zoom handle



Click-stop mechanism (SZX7)



Zoom knob stopper (SZ61/SZ51)



Eyepiece lock



Ground wire connection (back side)

OLYMPUS light solutions maximizes visibility in different tasks

OLYMPUS offers a range of light solutions perfectly tuned to the optical system of the zoom stereo microscope, to maximize the visibility of even minute characteristics.


The new LED integrated reflected/transmitted illumination stand

The world's first universal reflected/transmitted light LED illumination stand brings together all the advantages of LED technology. It allows the simultaneous use of reflected and transmitted illumination, and can alter their respective intensities continuously and separately by means of convenient dials on the stand. The use of super slim, high-brightness LED's successfully integrates transmitted illumination in a very slim base just 25mm thick that allows easy specimen access and manipulation. The complete microscope including LED integrated stand is extremely lightweight, compact and easy to carry.

Universal reflected illumination systems

Fiber optic illumination systems offer the highest illumination quality and flexibility. OLYMPUS offers a compact, cost effective 22W light source (SZ2-LGB) and a 100W light source (LG-PS2*) for professional use. Homogeneous illumination can be achieved by a ring light. For special contrast effects on free form 3D shapes, OLYMPUS offers a choice of single and double self supporting spot illumination fiber guides and precisely adjustable flexible fiber guides.


*An equivalent model may be offered in some markets.



Homogeneous light

Transmitted light illumination systems

For all transparent materials as well as for background illumination for the inspection of through holes, the OLYMPUS choice of illumination stands ranges from simple brightfield/simple oblique (SZX-ILLK) up to brightfield/darkfield (SZX-ILLD2) and brightfield/oblique Koehler (SZX-ILLB2) illumination models. Also available is a brightfield/oblique illumination attachment (SZ2-ILA) that can accommodate various light sources including a 100W halogen lamp housing.




Darkfield light

Special Illumination Techniques

Looking into holes

OLYMPUS offers effective coaxial illuminators for the SZX7 (SZX-ILLC) and the SZ61/SZ51 (SZ2-ILLC) which direct the light through the microscope's optical axis onto the specimen.



Coaxial light

Mirrored Surfaces

The illumination of highly reflective specimens needs special techniques in order to avoid disturbing light reflections. For spot and ring light illuminators as well as for coaxial



Polarized light.



illuminators, OLYMPUS offers dedicated polarizing equipment which eliminates such light effects (LG-R66PL for ring light illumination).

Making stress in transparent materials visible

Also available are simple and advanced transmitted illumination stands with polarizing equipment (SZX-AN, SZX-POL and SZ-POL2) for the efficient evaluation of tensions in transparent materials like plastic and glass. Their ease of use allows continuous, reliable production control of processes like injection molding.

Others:

- Fluorescence excitation illuminator SZX-RFL2 (OLYMPUS offers dedicated filter sets for the inspection of resist, concrete and microcracks)



Flexible angle of LED light source



Homogeneous, single and double spot illuminations fiber optic systems



Transmitted and coaxial illuminations with fiber optic systems High power fiber optic illumination system

Digital imaging



SZX7+SZX-TR30+DP70

Digital camera DP70 (SZX7, SZ61-TR)

By combining Olympus digital camera technologies originally developed for the consumer market with special high-speed processing hardware, images with up to 12.5 million pixels can be captured at high speed (around 3 seconds) while fully maintaining image quality, accuracy and color fidelity. The DP70 employs a 2/3 inch CCD.

Microscope digital camera DP12 (SZX7, SZ61-TR)

Compact overall design, with palm-size multi-function control unit integrating a 3.5" LCD monitor with 200,000-pixel display, and a small footprint that makes it easy to install and lay out any necessary auxiliary equipment. The 3.34 million-pixel and 1/1.8 inch progressive scanning CCD system ensures highly precise digital images which can be stored at a maximum resolution of 2048x1536.



SZ61+CAMEDIA Micro Imaging System

CAMEDIA Micro imaging system

A simple adapter enables an Olympus CAMEDIA digital camera to be attached to the eyepiece of a binocular body — an easy, practical and cost-efficient means of obtaining digital images.

Wide range of accessories to meet the needs of every application

Easy mounting with other equipment (bonder and prober arms)

The SZX7, SZ61 and SZ51 are designed to be integrated into process equipment. OLYMPUS offers various bonder and prober arms for all common brands.



① B & L style bonder arm / SZ-STB1 ② Bonder arm / SZ-STB2 ③ Bonder arm / SZ-STB3
④ Prober arm / SZ-STP ⑤ Arm / SZ-ST5 ⑥ Adapter for B & L bonder arm / SZ-BLAD



Ergonomic low positioned focus handles

With the focusing unit SZ2-FO, focus adjustment can be done with the hands resting on the work surface. The action of focusing requires minimal force as the microscope zoom body does not need to be moved. This allows prolonged work on difficult samples without fatigue.



SZ2-FO

Various universal stands

A variety of universal stands are available for the observation of large size specimens. No matter how big the samples are or how much they vary in size, OLYMPUS has the right choice of stands to suit any requirements.



SZX7+SZ2-STU-2



SZ61+SZ2-STU-3

■ SZX7 specifications

Item	Specifications			
Zoom microscope body SZX-ZB7	Zoom drive: Horizontal knob system Click stop for each zoom magnification: ON-OFF switching possible Zoom ratio values: 1:7 (0.8x to 5.6) Zoom magnification indication: 0.8, 1, 1.25, 1.6, 2, 2.5, 3.2, 4, 5, 5.6 Objective mounting: Screw mounting into thread <i>Lead-free materials used</i>			
Aperture iris diaphragm control: The AS unit (SZX-AS) is mountable				
Observation tube SZX-BI45 SZX-TBI SZX-TR30	SZX-BI45	SZX-TBI	SZX-TR30	
	Binocular tube Tilting angle 45° <i>Lead-free materials used</i>	Tilting binocular tube Tilting angle 5° to 45°	Trinocular tube Tilting angle 30° Light path selection:2 steps (Binocular 100%, Video & photo 80%/Binocular 20%)	
Interpupillary distance adjustable range: 50 to 76 mm Eyepiece clamping knob provided				
Stand SZ2-ST SZ2-ILST	SZ2-ST		SZ2-ILST	
	Standard stand		LED reflected/transmitted illumination stand	
Frame installation	Mounting diameter 76mm			
	Focusing adjustment Knob rotation tension adjustment Focusing stroke 120mm			
	Stage plate SZ2-SPBW (Black & white) SP-C (Glass clear transparent)		Clear glass plate in 100 mm dia. (SP-C) included.	
	Light source <i>Fiber optic illumination system</i> SZ2-LGB mountable (option) Transmitted light illumination attachment (SZ2-ILA) mountable (option)			
		Transmitted illumination: LED Reflected illumination: LED Average LED life span: 6000 hrs. Input rating: 100-120V/200-240V~0.15/0.1A, 50/60Hz		
Objective lens *The SZ2-ET auxiliary sleeve is required when the SZ2-ST/SZ2-ILST is used.	Model		Working distance	
	DFPLO.5x-4 DFPLO.75x-4 DFPLAPO1x-4 SZX-ACH1x SZX-ACH1.25x DFPL1.5x-4 DFPL2x-4 <i>All objectives: lead-free materials</i>		171mm 116mm 81mm 90mm 68mm 45.5mm 33.5mm	
Eyepieces "ComfortView" WHSZ series <i>All eyepieces: lead-free materials</i>				
Weight*	Configuration 1	4,380g	5,420g	5,220g
	Configuration 2	5,180g	6,220g	6,020g

Configuration 1: SZX-ZB7 + DFPLAPO1x-4 + individual observation tube + WHSZ10x-H (2) + SZ2-ST

Configuration 2: SZX-ZB7 + DFPLAPO1x-4 + individual observation tube + WHSZ10x-H (2) + SZ2-ILST

■ SZ61/SZ51 specifications

Item	SZ61	SZ61-60	SZ61-TR	SZ51	SZ51-60
Microscope body	Magnification				
	0.67x to 4.5x				
	Zoom ratio				
	1: 6.7				
	Working distance				
	110mm				
	Tube tilting angle				
	45° 60° 45° 60°				
Interpupillary distance adjustment	Left/right interlocked Adjustment range: 52 to 76 mm (using the WHSZ10X eyepieces)				
	Video camera adaptability				
— C-mount (0.5x built in) —					
Zoom adjustment knob					
Left/right single-shaft horizontal knob Interpupillary distance adjustable range: 50 to 76mm (using WHS10X-H)					
Optical components					
<i>Lead-free materials used</i>					
Auxiliary objective Mounting by screwing into the thread at the bottom of frame (M48 thread x0.75)					
Eyepiece "ComfortView" WHSZ series <i>Lead-free materials used</i>					
Stand SZ2-ST SZ2-ILST	SZ2-ST			SZ2-ILST	
	Standard stand			LED reflected/transmitted illumination stand	
Frame installation	Mounting diameter: 76mm				
	Focusing adjustment				
	Focusing stroke: 120mm				
	Stage plate		SZ2-SPBW (Black & white for anti-ESD) SP-C (Clear glass plate)		Clear glass plate in 100 mm diameter (SP-C) included
Light source			Oblique nicholas illumination LSGA mountable (option) Transmitted light illumination attachment (SZ2-ILA) mountable (option)		
			Transmitted illumination: LED Reflected illumination: LED Average LED life span: 6000 hrs. Input rating: 100-120V/200-240V ~0.15/0.1A, 50/60Hz		
Weight*	3,250g		3,720g		3,520g
	Zoom body only 1,300g		1,500g		1,300g

* Configuration: Zoom body + WHSZ10X-H(2) + SZ2-ST

■ "ComfortView" WHSZ eyepiece

	F.N.	Diopter adjustment	Reticle	Focal magnification
WHSZ10x	22	—	N.A.	—
WHSZ20x	12.5	—	N.A.	—
WHSZ10x-H	22	-8+5	Yes*	—
WHSZ15x-H	16	-8+5	Yes*	—
WHSZ20x-H	12.5	-8+5	Yes*	1.3x
WHSZ30x-H	7	-8+5	Yes*	2x

*Applicable reticle size: 24mm diameter, t1.5

■ Auxiliary objective for SZ61/SZ51

	Working distance (mm)
110AL0.25x	400
110ALK0.3x	250-350
110ALK0.4x	180-250
110AL0.5x	200
110AL0.62x	160
110AL0.75x	130
110AL1.5x	61
110AL2x	38

■ SZX7 optical performance

Eyepiece	WHSZ10x-H WHSZ10x		WHSZ15x-H		WHSZ20x-H		WHSZ30x-H WHSZ20x	
	F.N.	22	16	12.5	7			
Objective lens	Total magnification	Field of view (mm)	Total magnification	Field of view (mm)	Total magnification	Field of view (mm)	Total magnification	Field of view (mm)
0.5x	4x-28x	55-7.8	6x-42x	40.0-5.7	8x-56x	31.3-4.5	12x-84x	17.5-2.5
0.75x	6x-42x	36.7-5.2	9x-63x	26.7-3.8	12x-84x	20.8-3.0	18x-126x	11.7-1.7
1x	8x-56x	27.5-3.9	12x-84x	20.0-2.9	16x-112x	15.6-2.2	24x-168x	8.8-1.3
1.25x	10x-70x	22-3.1	15x-105x	16.0-2.3	20x-140x	12.5-1.8	30x-210x	7.0-1.0
1.5x	12x-84x	18.3-2.6	18x-126x	13.3-1.9	24x-168x	10.4-1.5	36x-252x	5.8-0.83
2x	16x-112x	13.8-1.9	24x-168x	10.0-1.4	32x-224x	7.8-1.1	48x-336x	4.4-0.63

■ SZ61/SZ51 optical performance

Microscope Body	Zoom magnification	WHSZ10x-H		WHSZ15x-H WHSZ10x		WHSZ20x-H		WHSZ30x-H WHSZ10x	
		F.N. 22		F.N. 16		F.N. 12.5		F.N. 7	
		Total magnification	Field of view (mm)	Total magnification	Field of view (mm)	Total magnification	Field of view (mm)	Total magnification	Field of view (mm)
SZ61	0.67x	6.7	32.8	10.1	23.9	13.4	18.7	20.1	10.4
	1x	10	22	15	16	20	12.5	30	7.0
	2x	20	11	30	8	40	6.3	60	3.5
	3x	30	7.3	45	5.3	60	4.2	90	2.3
	4.5x	45	4.9	67.5	3.6	90	2.8	135	1.6
SZ51	0.8x	8	27.5	12	20	16	15.6	24	8.8
	1x	10	22	15	16	20	12.5	30	7.0
	2x	20	11	30	8.0	40	6.3	60	3.5
	3x	30	7.3	45	5.3	60	4.2	90	2.3
	4x	40	5.5	60	4.0	80	3.1	120	1.8

* No auxiliary objective lens is attached


■ Fiber optic illumination system

Item	Specifications				
Type of illumination method	Homogenous	Double spot	Double spot	Single spot	Single spot
Type of fiber optic	SZ2-LGR SZ2-LGDI SZ2-LGDF SZ2-LGSI SZ2-LGSF				
Tube	Type Length	Flexible 800mm	Interlocked (self supporting) 500mm	Flexible 400mm	Interlocked (self supporting) 500mm Flexible 400mm
Fiber	Type	Multi-component LB56N equivalent, 50mm diameter			
	N.A.	0.56			
Bundle diameter	Input end	8mm	5.65mm	5.65mm	4mm 4mm
	Output end	70 x 0.22mm	4mm	4mm	4mm 4mm
Minimum bending radius	30mm		65mm	30mm	65mm 30mm

■ Compact halogen light source SZ2-LGB


Item	Specifications
Dimensions and weight	90(W) x 153 (H) x 100(D) mm, 600g (AC adapter 200g)
Rated voltage	AC adapter: input/100-240V/50/60Hz, output/ 12VDC2A
Power consumption	22W
Bulb type	12V22W halogen bulb with mirror
Bulb model	JCR12V22WA/3 (Philips 7724)
Average life span of bulb	2500 hours (minimum)
Light intensity adjustment	Voltage adjustment (3 steps)
Applicable stand	SZ2-ST

■ SZ61/SZ51 system diagram




*1 Please contact the nearest Olympus dealer for applicable models. *2 SZX-P400 and SZX-P600 can be attached to the transmitted light illuminators.

SZ2-LGB




Florescence illumination



*3 Other systems are offered in some areas.

LSGA




*4 IHA is mountable to SZ2-ST, SZ2-STB1, SZ2-STB3, SZ2-ST3 and TL-3.

*5 IHD is mountable to SZ2-STB1, SZ2-STB3 and SZ2-ST3.


*6 IHE is mountable to SZ2-ST.

■ SZ61/SZ51 dimensions


SZ61/SZ51



SZ61-TR



SZ61-60/SZ51-60



SZ61+SZ2-ST/SZ51+SZ2-ST

