

Cut-off Wheels



Cut-off wheels for all applications offering superior preparation quality, faster results and better cost-efficiency



Struers cut-off wheels are specially developed for materialographic specimen preparation. Our range of cut-off wheels are under constant improvement and are giving you:

- Specimens that are in perfect condition for the next preparation step with no thermal damage.
- A complete product programme covering all materials and materialographic applications.
- Intelligent wheels with the abrasive density varying across the wheel radius. The result is controlled cutting and uniform results.
- 3D wheels offering less heat damage due to more efficient cooling. In addition the 3D surface means less cutting debris and easier cleaning of the equipment.
- Specimens in a shorter time and at a lower cost per sample.



Cutting: The first step in the materialographic process

The first step in a process sets the pace and determines the quality of the finished result. In the materialographic process, the first step is most often cutting. The purpose of cutting is to section a representative, yet manageable sample from a large or irregular piece of a given material or to obtain sections at specific angles, e.g. cross-sections. Cutting makes high demands on a number of factors: Speed, planeness, amount of thermal damage and degree of deformation.

About abrasive wet cutting

The most commonly used method to section a material is abrasive wet cutting. The cut-off wheels consist of two main components: abrasives and binders. During cutting, the cut-off wheel is flushed with a cooling liquid to avoid thermal damage and to remove debris, providing the highest possible material removal.

A complete product range

Struers cut-off wheels have been specially developed for materialographic specimen preparation: they produce specimens that are in perfect condition for the next preparation step. Our large range of different wheels assures that all materials can be cut without structural changes due to overheating or deformation, and guarantees maximum life time of the wheels.

The wheels are designed for Struers machines, taking into consideration the most recent developments in wet cutting techniques. Various abrasives are used for the cutting of different materials. However, Al_2O_3 or SiC in a resin bond is used for cutting most metals.

The selection of bond hardness must be based on an evaluation of the hardness of the material. Soft materials should be cut with cut-off wheels having a hard bond as the abrasive grains retain their cutting ability for a long time. Harder metals require a softer resin bond,

which gives a fast replacement of abrasive grains. For

the cutting of materials with hardness above HV 700, diamond or CBN (cubic boron nitride) are used as the abrasive. Because of the high cost of these abrasives only the outer rim of the wheel is covered with abrasive particles in a resin or a metal bond. Metal bonded wheels are used for cutting of brittle materials, such as ceramics or minerals, while bakelite bonded wheels are used for more ductile materials, such as sintered carbides or composites containing predominantly hard phases.

Intelligent cut-off wheels

With cut-off wheels from Struers the abrasive density varies across the wheel radius – with increasing density towards the center of the wheel. This means that the cutting performance of the wheel remains constant even as it wears to a smaller diameter (please see illustration on page 4).

As a conventional cut-off wheel with uniform abrasive density wears, the cutting performance changes from the outside to the inside. The number of grains is reduced, the load of each grain increases and the wheel appears to get softer and softer. The drawback is higher wear and a less controllable cut.

3D cut-off wheels for increased cutting performance



Struers cut-off wheels with a hexagonal surface pattern are an addition to our standard line of cut-off wheels. The cut-off wheels are designed so that each side has a 3 dimensional hexagonal surface pattern, also called the 3D surface.

With the 3D cut-off wheels cooling of the workpiece is much more efficient. As the aim in materialography is to obtain the true, undisturbed structure less heat damage due to more efficient cooling is an important step towards faster, more reliable preparation results.

In addition, with the 3D design the problem of cutting debris building up during cutting is completely eliminated. The cutting table and the entire cutting chamber stay clean as the small particles easily are washed away. Cleaning of the equipment is far easier, and the risk of overflowing because of a blocked outlet is greatly reduced.

Cost efficiency

Selecting the right cut-off wheel is not just a matter of preparation quality, it is also the best way to save time and consumables. Choosing the correct wheel for an application will produce a surface which requires less subsequent preparation steps. Thus producing specimens in a shorter time and at a lower cost per sample.




With the 3D surface all the water sprayed into the channels between the hexagons is transported into the cut, thus cooling the workpiece much more efficiently

To select the correct cut-off wheel:

Struers offers a wide variety of wheels, which means that you can select the hardness that optimally balances durability with finish.

If the hardness of the material is known, use the table at the top of the page. In the table at the bottom, you will then find the cut-off wheel codes for the specific cutting machines. If the hardness of the material is not known, find a suitable cut-off wheel according to material group in the table below.

1. Go upwards on the y-axis of the overview to the right until you find the hardness value of your material.
2. Move to the right, until you cross the cut-off wheel that fits your application. If you only have one material to cut, find the wheel where your material's hardness is placed as close to the middle as possible. For two or more materials, see if you can find a wheel that covers the whole hardness range. The bars that faded out at the bottom represent wheels that can be used for lower hardness also. However, this is not a very economical solution, and it should only be used in exceptional cases.
3. Find the number (I-XI) of the respective wheel, and see the table below for the code of the correct wheel for your cut-off machine.



Cut-off machine	Std. wheel size* (mm)											
Exotom-100/-150	432 x 3.0 x 32	10S43	10S43		30A43	40A43 42A43 ¹⁰	50A43 52A43 ¹⁰	60A43 62A43 ¹⁰	108MA ¹	26EXO ²	MOD35 ²	89EXO ³
Axitom (1,950 rpm)	350 x 2.5 x 32	10S35	20S35	20A35	20A35	30A35	40A35	50A35 56A35 ¹²	88EXO ⁶	26EXO ²	MOD35 ²	89EXO ³
Exotom/Unitom-2/-5/-50 (2,775 rpm)		10S35	30S35	20A35	30A35	40A35	50A35 56A35 ¹²	60A35 66A35 ¹²	88EXO ⁶	26EXO ²	MOD35 ²	89EXO ³
Unitom/Discotom-50/-60/-65	300 x 2.0 x 32	10S30	20S30		30A30	40A30	50A30	60A30	58UNI ⁴	25EXO ⁴	55UNI ⁵	59UNI ⁵
Discotom-5/-6/Labotom-3	250 x 1.5 x 32	10S25	20S25	20A25	30A25 33A25 ⁹	40A25 46A25 ¹²	54A25 50A25 ¹¹ 56A25 ¹²	60A25 66A25 ¹²	B0C25 ⁷	24TRE ⁸	25TRE ⁸	E0D25
Discotom/Labotom	235 x 1.5 x 22	10S24	20S24		30A24	40A24	50A24	60A24				
Discoplan-TS	200 x 1.0 x 22									23TRE	M4D20	

1) 406 x 1.8 x 32 2) 350 x 1.5 x 32 3) 356 x 1.5 x 32 4) 305 x 1.8 x 32 5) 305 x 1.5 x 32 6) 356 x 1.8 x 32 7) Width = 1.3 8) Width = 1.1 9) Width = 0.8 10) Fibreglass reinforced
11) For hard and ductile materials, Ni-base alloys 12) 3D cut-off wheels 13) Width=0.6

Precision cut-off machine	Std. wheel size* (mm)											
Secotom-1/-10**	200 x 0.8 x 22	10S20	10S20	30A20	30A20	656CA	656CA	656CA	655CA	652CA	630CA ¹³ 631CA ¹³	E0D15
Accutom-5/-50	150 x 0.5 x 12.7	10S15 370SA	10S15	40A15 30A15	40A15 30A15	50A15	50A15	50A15	455CA	452CA	430CA 431CA	E0D15 370SA
Accutom-2	125 x 0.5 x 12.7	30A13	30A13	30A13	30A13	50A13	50A13	50A13	355CA	352CA	330CA 331CA	331CA
Minitom	125 x 0.5 x 12.7	331CA	331CA	355CA	355CA	355CA	355CA	355CA	355CA	352CA	330CA 331CA	331CA
Wheels with special sizes	100 x 0.3 x 12.7	These wheels can be used on both Accutom-2,-5,-50 and Secotom-10 for cutting of small specimens where high precision or minimum material loss is required									230CA 231CA	231CA
	75 x 0.15 x 12.7										100CA 101CA	101CA

*) Diameter x Width x Bore in mm, **) On Secotom-1 only use 630CA + 652CA

Struers A/S

Pederstrupvej 84
DK-2750 Ballerup, Denmark
Phone +45 44 600 800
Fax +45 44 600 801
struers@struers.dk



USA

Struers Inc.
24766 Detroit Road
Westlake, OH 44145-1598
Phone +1 440 871 0071
Fax +1 440 871 8188
info@struers.com

CANADA

Struers Ltd.
7275 West Credit Avenue
Mississauga, Ontario L5N 5M9
Phone +1 905-814-8855
Fax +1 905-814-1440
info@struers.com

SWEDEN

Struers A/S
Ekbacksvägen 22, 3 tr
P.O. Box 11085
SE-168 69 Bromma
Telefon +46 (0)8 447 53 90
Telefax +46 (0)8 447 53 99
struers@struers.dk

FRANCE

Struers S.A.S.
370, rue du Marché Rollay
F- 94507 Champigny
sur Marne Cedex
Téléphone +33 1 5509 1430
Télécopie +33 1 5509 1449
struers@struers.fr

NEDERLAND/BELGIE
Struers GmbH Nederland
Electraweg 5
NL-3144 CB Maassluis
Tel. +31 (0) 10 599 72 09
Fax +31 (0) 10 599 72 01
glen.van.vugt@struers.de

BELGIQUE (Wallonie)

Struers S.A.S.
370, rue du Marché Rollay
F- 94507 Champigny
sur Marne Cedex
Téléphone +33 1 5509 1430
Télécopie +33 1 5509 1449
struers@struers.fr

UNITED KINGDOM

Struers Ltd.
Unit 25a
Monkspath Business Park
Solihull
B90 4NZ
Phone +44 0121 745 8200
Fax +44 0121 733 6450
info@struers.co.uk

IRELAND

Struers Ltd.
Unit 25a
Monkspath Business Park
Solihull
B90 4NZ
Phone +44 (0)121 745 8200
Fax +44 (0)121 733 6450
info@struers.co.uk

JAPAN

Marumoto Struers K.K.
Takara 3rd Building
18-6, Higashi Ueno 1-chome
Taito-ku, Tokyo 110-0015
Phone +81 3 5688 2914
Fax +81 3 5688 2927
struers@struers.co.jp

CHINA

Struers Ltd.
Office 702 Hi-Shanghai
No. 970 Dalian Road
Shanghai 200092, P.R. China
Phone +86 (21) 5228 8811
Fax +86 (21) 5228 8821
struers.cn@struers.dk

DEUTSCHLAND

Struers GmbH
Karl-Arnold-Strasse 13 B
D-47877 Willich
Telefon +49 (0)2154) 486-0
Telefax +49 (0)2154) 486-222
verkauf.struers@struers.de

ÖSTERREICH

Struers GmbH
Zweigniederlassung Österreich
Ginzkeyplatz 10
A-5020 Salzburg
Telefon +43 662 625 711
Telefax +43 662 625 711 78
stefan.lintschinger@struers.de

SCHWEIZ

Struers GmbH
Zweigniederlassung Schweiz
Weissenbrunnstrasse 41
CH-8903 Birmensdorf
Telefon +41 44 777 63 07
Telefax +41 44 777 63 09
rudolf.weber@struers.de

CZECH REPUBLIC

Struers GmbH
Organizační složka
Havlíčková 361
CZ-252 63 Roztoky u Prahy
Tel: +420 233 312 625
Fax: +420 233 312 640
david.cernicky@struers.de

POLAND



Struers Sp. z o.o.
Oddział w Polsce
ul. Lirowa 27
PL-02-387 Warszawa
Tel. +48 22 824 52 80
Fax +48 22 882 06 43
grzegorz.uszynski@struers.de

HUNGARY

Struers GmbH
Magyarországi fióktelep
Puskás Tivadar u. 4
H-2040 Budaörs
Phone +36 (23) 428-742
Fax +36 (23) 428-741
zoltan.kiss@struers.de

SINGAPORE

Struers A/S
627A Aljunied Road,
#07-08 BizTech Centre
Singapore 389842
Phone +65 6299 2268
Fax +65 6299 2661
struers.sg@struers.dk



Constant improvement

Struers cut-off wheels offer the widest variety of abrasive types and bond properties, allowing you to find the optimal wheel for all materials and materialographic applications.

At Struers, we are constantly striving to develop new improved and environmentally friendly consumables. To you this means superior preparation quality, faster results and better cost-efficiency. Make your lab more efficient, more productive and successful with performance products from Struers.

For more information on our cut-off wheels and other consumables, please ask your local Struers representative or read more on www.struers.com.



The Struers cut-off wheels are boxed with cardboard flanges and detailed instructions